







Model	Stroke (mm)	Lead (mm)	Maximum payload (kg)					Maximum speed (mm/s)	Position repeatability (mm)	Motor output	Axis	Driving method
			Horizontal			Vertical						
			Slide/Rod (type)	Table (type)								
	*1	*2		*3								
 BAC5D 50 to 500 (50 mm increments)	12	3	-	-	-	1.5	800	±0.02	50W AC servomotor	X-axis	Ball screw	
	6	6	-	-	-	3.0	400					
 BAC7D 50 to 500 (50 mm increments)	12	6	-	-	-	1.5	800	±0.02	50W AC servomotor	X-axis	Ball screw	
	6	12	-	-	-	4.0	400					
 BAC5D(T) 50 to 500 (50 mm increments)	12	-	3	2	-	1.0	800	±0.02	50W AC servomotor	X-axis	Ball screw	
	6	-	5	3.0	-	2.5	400					
 BAC7D(T) 50 to 500 (50 mm increments)	12	-	5	3	2	1.5	800	±0.02	50W AC servomotor	X-axis	Ball screw	
	6	-	9.0	6	4	3.5	400					
 BAC3D 50 to 500 (50 mm increments)	12	3.2	-	-	-	1.5	600	±0.02	50W AC servomotor	X-axis	Ball screw	
 BAC4D 50 to 500 (50 mm increments)	12	5.6	-	-	-	3.0	600	±0.02	50W AC servomotor	X-axis	Ball screw	